

Hose Tester / Pressure Washer



HT-100

Our HT 100 is easy to use, comes standard with four outlets, stainless steel ball valves, 3 gallons a minute at 600 PSI. Capable of testing up to 6" diameter hose, and up to 300 ft per discharge.

Also included is a built-in pressure washer, includes 25 ft of 3/8 non marking hose with quick release, heavy duty wand & handle, a quick connect injector and metering valve for adding cleaning agents to water supply, stainless steel nozzle with stream straightener. Comes standard with our easy to use wheeled cart, fits through a standard 36" door way. Pressure washer can be removed from test stand for ease of use.

Product Specifications

- Pressure Washer System included
- Complies with NFPA standards
- 1-1/2" connection standard or 2-1/2" connection optional
- Built-in Pressure Washer
- Built-in Tool Tray
- Stainless Steel Ball Valves
- 3 Gallons a Minute at 600 PSI
- Capable of Testing up to 6" dia. Hose
- 300 ft. per Discharge
- Built-in Pressure Washer
- 25 ft of 3/8 Non-Marking Hose
- Heavy Duty Wand & Handle
- Quick Connect Injector and Metering Valve for Adding Cleaning Agents
- Wheeled Cart
- Standard 36" Door Way



Quality Products
Used Worldwide
Since 1988

208 Industrial Blvd.
Waconia, MN 55387
(952) 442-2977 Business
(800) 233-1561 Toll Free
(952) 442-4106 Fax
www.flamefighter.com
sales@flamefigher.com